




Office Lighting Liner Light

Laila VLL001/53W

Linear lighting fixture with antiglare front trim for pendant installation. Suitable for offices and where the glare need to be low. The luminaire produce direct light down for the operative position, and indirect light up for the diffuse soft illumination of the space. Housing made of extruded aluminum with highly pure powder coating. Available in white (RAL 9003), black(RAL 9005) and grey aluminum (RAL9006) color. Reflector in vacuum aluminum plated PC. UGR≤ 19. The led driver is included and internal to the fixture. The lumen output is based on 3000K(CRI80) led.

Product information

Installation:	Pendant
Material:	Aluminum
Painting:	Highly pure powder coating
System power (W):	53W
Fixture lumen output (lm):	4000
System efficiency (lm/W):	80
Power supply:	Included



1263 x 70 x 41 mm

Light source information

Led Type: SMD

Led power consumption (W):	53W
Led lumen output (CRI80):	6360
Led efficiency (lm/W):	120
LED Power:	53W

Packaging

Net weight (kg):	2.3
Gross weight multiple packaging (kg):	10.2
Dimesions multiple packaging (mm):	1220x140x200
Products quantity multiple packaging:	4

Code composition


Model	Power	CRI RA	CTT K	Beam °	Color	Cover	Dimming
VLL001/53	53W	82 >82	30 3000	15	WH White	Clear	On-Off
W		SDCM 3	40 4000	30	SG Grey	Frosted	DALI
		92 >92	50 5000	45	BK Black		0-10V
		SDCM 3					

Example: Name-10W-9240-45-BK-Clear-on-off

In the sample above you compose:

VLT525-10-10watts-CRI>92 4000K-45° Beam angle-Black-Clear cover-On-Off version UGR \leq 21
220-240V 90° 355° IP20

OPTIONAL



Graphic visualization of the light flow in the space.

Vianolux has the right to update the product and its performance without to make any communication.

The product specifications may change after update.

VIANOLUX

No.25 Liandu Road, Leliu Town, Shunde District,
Foshan city, Guangdong, China
PHONE: 0086 0757-22681858
EMAIL: sales@vianolux.com