




Recessed

Ela VLD802/42W

Slim downlight for recessed installation in ceiling. Available in 6 powers and 3 dimensions. Housing made of die casting aluminum with highly pure powder coating. Available in white (RAL 9003), black (RAL 9005) and grey aluminum (RAL9006) color. It mounts COB led. Reflector in specular silver anodized aluminum. UGR \leq 22. The led driver is included and external to the fixture. Clear or frosted shade optional can be ordered. Fixing system by springs. The lumen output is based on 3000K (CRI80) led.

Product information

Installation:	Recessed
Material:	Aluminum
Painting:	Highly pure powder coating
System power (W):	42W
Fixture lumen output (lm):	3780
System efficiency (lm/W):	90
Power supply:	Included



Cut out: Ø200mm

Light source information

Led Type: COB

Led power consumption (W):	42W
Led lumen output (CRI80):	5040
Led efficiency (lm/W):	120
LED Power:	42W

Packaging

Net weight (kg):	0.97
Gross weight multiple packaging (kg):	20.4
Dimesions multiple packaging (mm):	650x485x490
Products quantity multiple packaging:	20

Code composition

Model	Power	CRI RA	CTT K	Beam °	Color	Cover	Dimming
VLD802/42 W	42W	82 >82 SDCM 3	30 3000 40 4000	60	WH White SG Grey BK Black	Clear Frosted	On-Off DALI 0-10V
		92 >92 SDCM 3	50 5000				

Example: Name-10W-9240-45-BK-Clear-on-off

In the sample above you compose:

VLT525-10-10watts-CRI>92 4000K-45° Beam angle-Black-Clear cover-On-Off version UGR \leq 21
220-240V 90° 355° IP20

Vianolux has the right to update the product and its performance without to make any communication.
The product specifications may change after update.

VIANOLUX

No.25 Liandu Road, Leliu Town, Shunde District,
Foshan city, Guangdong, China
PHONE: 0086 0757-22681858
EMAIL: sales@vianolux.com